


R/W CORE MODULE MD770R



APPLICATIONS

Mobile Devices, Portable Game Machines, Mobile Phones, PDA Various Security System, Hotel and Door Key Key Board, USB Device and Authentication Equipment

SPECIFICATIONS

Model	MD(TJ)-770R
Dimension	9mm x 9mm x 2.0mm (min)
Operating Frequency	13.56MHz±7KHz
Supported IC Cards / Tags	ST LR,I-CODE1,I-CODESLI,Tag-It HF-I,My-D ISO/IEC 15693,ISO/IEC 18000-3 MODE1
Operating Distance	0 – 120mm
Interface	Serial (CMOS)
Power Supply	DC2.7~5.0V ±5%
Power Consumption	<10mA Carrier ON <8.5mA Carrier OFF <10µARW Power Down
Operating Temperature	-10C~+50C

Data Sheet Version	MD770R
Date	09 May 2013

A Product of:



MDT INNOVATIONS SDN. BHD.
Suite 19-04A, The Pinnacle Persiaran Lagoon, Bandar
Sunway 46150 Petaling Jaya, Malaysia.
TEL: +60(3) 7610 2988
FAX: +60(3) 7610 2999
EMAIL: contact@mmdt.cc



All rights reserved.
Product specification are subject to change without prior notice.