

Mi360 HIGH GAIN DIRECTIONAL PANEL ANTENNA



SPECIFICATION

Product Code	UHF-Antenna2
Frequency	2400 – 2500 MHz
Gain	12 dBi
VSWR	2.0 : 1 (Max)
Polarization	Linear, Vertical
HPBW / Horizontal	84°
HPBW / Vertical	23°
Front to Back Ratio	15 dB
Downtilt	10 W (cw)
Impedance	50 ohm
Connector	SMA Jack
Survival Wind Speed	216 km/hr
Temperature	-40°C + 80°C
Humidity	95% R.H. @ 55°C
Lightning Protection	DC Ground
Radome Color	White
Radome Material	ABS, UV Resistant
Weight	0.2 kg
Dimensions	327 x 80 x 22 mm

Data Sheet Version	UHF-Antenna2
Date	02 October 2015

* Specifications and product availability subject to change without prior notice.

A Product of:



MDT INNOVATIONS
www.mmdt.cc

MDT INNOVATIONS SDN. BHD.

Suite 19-04A, The Pinnacle Persiaran Lagoon, Bandar
Sunway 46150 Petaling Jaya, Malaysia.
TEL: +60(3) 7610 2988
FAX: +60(3) 7610 2999
EMAIL: contact@mmdt.cc



All rights reserved.
Product specification are subject to change without prior notice.